NASA Contractor Report 172412

HOOP/COLUMN ANTENNA

RF VERIFICATION MODEL

VOLUME I: TEST RESULTS

W. F. Croswell (Editor), M. D. Vanstrum,
R. J. Schrimpf, R. G. Taylor, and R. L. Moye

HARRIS CORPORATION
Melbourne, Florida

NASA

National Aeronautics and
Space Administration

Langley Research Center
Hampton, Virginia 23665

HOOP/COLUMN ANTENNA

RF VERIFICATION MODEL

ANALYSIS AND TEST

BY

HARRIS CORPORATION

GOVERNMENT ELECTRONIC SYSTEMS DIVISION

PREPARED FOR: LANGLEY RESEARCH CENTER

UNDER CONTRACT NAS1-15763

EDITOR: W. F. Croswell, Section Head

AUTHORS: M. D. Vanstrum, Senior Engineer

R. J. Schrimpf, Senior Engineer

R. G. Taylor, SAPE

R. L. Moye, Lead Engineer

TABLE OF CONTENTS

VOLUME I

NOTE:

ANALYSIS AND CORRELATION DATA FOR HOOP/COLUMN ANTENNA
RF VERIFICATION MODEL FINAL REPORT COMPRISE VOLUME II.

LIST OF FIGURES

HOOP/COLUMN ANTENNA RF VERIFICATION MODEL
ANALYSIS AND TEST

INTRODUCTION

The purpose of this report is to present the results of an experimental and theoretical study of the RF characteristics of the Hoop/Column quad aperture antenna. The primary purposes of the RF Verification Model in the LSST Program were twofold.

1) To provide experimental pattern data for the quad aperture configuration at different reflector edge illumination levels from which the geometry and edge effects can be assessed. Also, to provide experimental data which can be compared with calculations using various theoretical reflector scattering formulations.

2) To experimentally determine the effects of scale model quartz cables, to be used in the hoop column design, upon secondary patterns in order to assess the importance of developing a scattering theory to predict such effects.

In addition to the description of experimental procedures and the presentation of extensive experimental results, a comprehensive theoretical study of how to feed the quad aperture configuration is described. Firstly, an outline of the physical optics formulation used for subsequent calculations is given. Secondly, the experimental feed horns were modeled, using a Huygen's source approximation. From these feed horn patterns, calculations for various experimental aperture configurations were made, and compared with experimental patterns. Using these data and measured raster scan contour plots, a fundamental effect of parasitic side lobes is discussed, including location in space, and reasons for the approximate amplitude.

Based upon these results, a comprehensive theoretical study was conducted in order to design a feed for use in the quad aperture configuration resulting in good pattern characteristics. The first feed studied was the corrugated horn, where contiguous cross track coverage suitable for a radiometric mission was considered. Next, the effect of feed aperture distributions upon the secondary gain and pattern characteristics was determined for a wide variety of typical low side lobe aperture distributions. Then, related to communications missions, a brief study was made of multimode horn feeds suitable for clusters. Finally, a discussion of feed designs suitable for the quad aperture is given, along with a brief summary of conclusions from the study.

DESCRIPTION OF TEST ARTICLES AND ALIGNMENT

A top-view drawing of the basic pie-shaped reflectors, support fixtures, and feed support plates are given in Figure 1. Notice that the center of rotation is located behind the vertex of the parabolas in order to balance the overall structure on the azimuth-elevation antenna mount. Front and side views of the structure are given in Figures 2, 3, and 4 where scale model quartz cables are shown attached to the antenna. It can be noted from these figures that the feed support and fixtures are located well below the primary apertures; the feed horn itself provides the only blockage area. Detailed sketches showing specific dimensions and angles are given in Figures 16 through 19. (See Volume II)

The reflectors, as shown in Figure 5, were fabricated on a mold with an accuracy of 0.002 inch. The surface was made conductive with a flame spray aluminum process. The final reflectors were checked on the backup structure with a swept template and shown to be accurate to within 0.008 inch rms.

The reflector and feed support assembly were hoisted in sections as shown in Figure 6 and assembled on the pedestal. A special alignment tool was

manufactured to check feed alignment. Three known points located by holes were placed in each sector during manufacture. With these holes and an alignment fixture the distance to the feed on focus can be set to an accuracy of 0.03 inch. By placing fine cross hairs in the feed horn aperture, and the input waveguide to the feed horn, angular alignment was obtained. The exact offset angle of 21.6 degrees was marked on the reflector surface. The feed horn alignment was determined by observing the input waveguide, with the mixer removed.

The transmitting antenna, and an alignment scope, are shown in Figure 8. The transmitting antenna, which is located at the top of the tower, was aligned by the double cross hair method used on the feed horn. This alignment permitted bore sighting within a distance of ±1.0 foot of the center axis of the two sectors as observed from the transmitting tower. The bore sight scope, as shown in Figure 8, permits the setting of the test antenna axis with errors of less than 0.004 degrees.

The quartz wires were mounted as required during the test program, using the fiberglass support fixture on the feed support structure, and special tabs attached around the edge of the dish, as shown in Figures 9 and 10. Also visible in Figure 10 are the standard gain horn, mounted on the feed support structure, and the white parabolic reflector used to obtain the phase reference for the two channel phase lock receiver.

DESCRIPTION OF THE TEST RANGE AND EQUIPMENT

The antenna test range equipment is illustrated in Figure 11. Most of the equipment is standard Scientific Atlanta and Hewlett Packard off-the-shelf instrumentation. Using analog-to-digital devices, the output of the synchros was digitized and recorded on floppy disks along with phase-amplitude data using a Vector computer. The data on the floppy disks were then transferred

off-line to the Harris H-80 and H-800 computers and stored. All of the
subsequent raster scan data shown in this report were obtained in this
manner. The basic pedestal gear and synchro accuracy was checked; hence the
recorded data from the synchros can be repeated by rotating the pedestal in
the same direction for each line of the raster scan run. The absolute
accuracy of any angular number recorded was better than 0.05 degrees. It was
noted that the stability of the amplitude recording system was better than
0.1 dB from day to day, as was the drift during any one 8 hour measurement
day.

The geometrical arrangement of the antenna range, along with a
conservative link budget, is given in Figure 12. It was noted during the
course of measurement that receiver noise began to be noticeable about 70 dB
down in dynamic range, although repeatable lobes were measured at lower
values. The multipath signal levels for the test antenna were determined
using the geometry of Figure 12, and the measured transmitting antenna pattern
given in Figures 13 and 14. The cross-polarization levels from the trans-
mitter were generally below -40 dB in the multipath reflection Fresnel zone.
The direct polarization pattern level in the same region will be -26 dB to
-30 dB down. The above mentioned measurements, along with the multipath zone
being 13 to 16 degrees away from any measurement elevation angle, indicate
that the multipath had minimal effect upon the detailed measurements reported.

DESCRIPTION OF EXPERIMENT AND CALIBRATION

The receiving feed antennas were specified to have -6 dB and -14 dB edge
tapers at the bisector of a pie reflector. The feed horns designed for use in
this experiment are depicted in Figure 15. A detailed set of primary patterns
were measured and recorded in both analog and digital form, as listed in the
pattern log, LSST-I, page 24. The analog patterns are shown on the pages as

listed in LSST-I. The feed horns were set at an angle of 21.6 degrees corresponding to bisector of the angle between the focal point and the outer edge of the pie sector. For convenience, the following are the summary parameters used in this experiment:

FOCAL LENGTH   137.7 inches

OFFSET ANGLE   21.6 degrees

RADIUS OF PIE SECTOR   110.8 inches

DIAMETER FROM FOCUS TO PIE EDGE   105.3 inches

OPERATING FREQUENCY   15.0 GHz

PHASE CENTER DISTANCE BEHIND HORN APERTURE

    -6 dB   0.30 inches

    -14 dB   0.99 inches

The antenna range was chosen to minimize multipath signals. The distance between the towers was approximately D^2/λ or about one-half the conventional range distance. In order to correct for quadratic phase error, due to a foreshortened range, the feed was displaced along the offset angle. Several calculations were run for symmetrical offset reflectors and compared with measurements where the axial feed displacement was varied. From these data, and gain measurements, it was determined that an axial defocus (movement along the offset angle of 21.6 degrees) of about 1.2 inches gave optimum gain. All of the data taken are given in the log, LSST-II, page 31, with the subsequent pages of patterns listed for indexing.

It should be noted that great care was taken to ensure calibration between pattern sets that were taken over a period of nearly five weeks. As a routine procedure, the pedestal was always rotated in the same direction during pattern taking. This tended to maintain gear wear errors in the same direction. Also, the systems were left on continuously to minimize warmup

errors, and there was a gain measurement taken by the substitution method before and after each measurement sequence. The only significant measurement error noted was the resetting of synchros to precise increments. This error, on an absolute basis, was less than 0.05 degree and was observable for only a few significant pattern locations. It was noticeable as an amplitude change on secondary peaks at wide angles. There was little chance of improving on the accuracy without a complete redesign and rebuild of the pedestal and synchro system.

Data were also taken for both no scan and scanned cases. For the scan cases the horn was mounted in a plane perpendicular to the offset angle of 21.6 degrees. The horns were scanned in the horizontal plane and toward the direction of the other pie sector. Data are presented in a three-dimensional azimuth-elevation-amplitude plot, followed by an azimuth-amplitude plot, and an elevation-amplitude plot for detailed review. The data presented allow for a detailed comparison of the aperture coupling problem between two pie-shaped sectors.

SUMMARY OF ANALOG PATTERN MEASUREMENTS

The purpose of presenting these results is to give an expanded pattern description of the aperture coupling and quartz wire effects over wide angular sectors. It should be noted that the quartz wires produced few noticable pattern changes, and hence no detailed raster scans were obtained. The secondary pattern log is given in LSST-IV through LSST-IX, pages 119-306. In order to compare one pattern set with another in absolute amplitude, the measured gain for that pattern set is available in the recorded floppy disk data.

HARDWARE DESCRIPTION AND ANALOG PATTERNS LOGS

The remainder of Volume I consists of photographs, hardware descriptions, and antenna patterns.

Figure 1.   TOP VIEW OF THE RF VERIFICATION MODEL

198.08

REFLECTOR

REFLECTOR BASE

FEED SUPPORT BEAMS

FEED SUPPORT PLATFORM

TWO HORN FEED

EXISTING PIPE PEDESTAL

221.529

110.692

SINGLE HORN FEED

Figure 2.   FRONT VIEW OF THE RF VERIFICATION MODEL

Figure 3. SIDE VIEW OF THE RF VERIFICATION MODEL

Figure 4.   ISOMETRIC VIEW OF THE RF VERIFICATION MODEL

FABRICATION OF
PRECISION RF
VERIFICATION MODEL

A MOLD WITH 0.05 mm
(0.002 IN.) RMS ACCURACY
IS USED TO BUILD
FIBERGLASS
FACE SKINS

FACE SKINS ARE
ASSEMBLED TO
RIGID BACKUP
STRUCTURE

ASSEMBLED
ANTENNA TEST
MODEL

ADJUSTMENT SCREWS
BETWEEN FACE SKINS AND
BACKUP STRUCTURE PROVIDE
A REFLECTOR ACCURACY OF
0.2 mm (0.008 IN.) RMS

Figure 5. PHOTOGRAPH OF THE REFLECTOR AND BACKUP
STRUCTURE AND ASSEMBLY DURING FABRICATION

Figure 6.   PHOTOGRAPH OF THE REFLECTOR STRUCTURE
BEING LIFTED ON THE ANTENNA RANGE

Figure 7.   PHOTOGRAPH OF FEED ALIGNMENT STRUCTURE
             BEING USED ON ANTENNA RANGE

Figure 8.   PHOTOGRAPH OF RF VERIFICATION MODEL LOCATED
ON ANTENNA RANGE SHOWING THE ALIGNMENT SCOPE
AND TRANSMITTING ANTENNA AND TOWER

Figure 9.   RF VERIFICATION MODEL SHOWING
             QUARTZ CORDS, FRONT VIEW

Figure 10.   RF VERIFICATION MODEL SHOWING
             QUARTZ CORDS, SIDE VIEW

FIGURE 11. ANTENNA RANGE EQUIPMENT DIAGRAM

SOURCE ANTENNA

TEST
ANTENNA

1088'

5.6°

150'

15.7°

54'

SPECULAR REGION

1084'

RANGE LINK BUDGET

SIGNAL SOURCE	+	8.0	dBm.
.141 COAX CABLE	–	5.0	dB.
SOURCE ANTENNA	+	31.0	dB.
RANGE LOSS	–	106.0	dB.
APC ANTENNA	+	33.0	dB.

REFERENCE CHANNEL

RECEIVED POWER	–	39.0	dBm.
RECEIVER SENSITIVITY	–	50.0	dBm.
MARGIN	+	11.0	dB.

TEST CHANNEL

RECEIVED POWER	–	22.0	dBm.
RECEIVER SENSITIVITY	–	90.0	dBm.
DYNAMIC RANGE		68.0	dB.

FIGURE 12.   RANGE GEOMETRY and LINK CALCULATIONS

Figure 13.   TRANSMIT ANTENNA PATTERNS, E PLANE-AZIMUTH CUT.

Figure 14.   TRANSMIT ANTENNA PATTERNS, H PLANE AZIMUTH CUT.

A) LARGE HORN
    14dB TAPER

.391

.311

1.00

2.13

5.00

.702

.622

2.90

.391

.311

1.00

1.45

3.13

B) SMALL HORN
    6dB TAPER

.702

.622

2.05

FIGURE 15.   FEED HORNS

tHARRIS CORPORATION
Government Systems Group

SIZE	CODE IDENT NO.		REV
A	91417		

LSST - I

PRIMARY PATTERN LOG

HORN	PLANE	POLARIZATION	FILE NAME	PAGE NUMBER
6 dB	E	CO	P0001	25
6 dB	E	X	P0002	25
6 dB	H	CO	P0003	26
6 dB	H	X	P0004	26
6 dB	45°	CO	P0005	27
6 dB	45°	X	P0006	27
14 dB	E	CO	P0007	28
14 dB	E	X	P0008	28
14 dB	H	CO	P0009	29
14 dB	H	X	P0010	29
14 dB	45°	CO	P0011	30
14 dB	45°	X	P0012	30

6dB HORN PRIMARY
E-PLANE AZ CUT
ϕ_c=-0.300"

CO-POL. : P0001
X-POL : P0002

-25-

6dB HORN PRIMARY
H-PLANE AZ CUT
ϕ_c=-0.300"

CO-POL. : P0003
X-POL. : P0004

6dB HORN PRIMARY
45° PLANE AZ CUT
$\phi_c = -0.300"$
CO-POL. : P0005
X-POL. : P0006

14dB HORN PRIMARY
E-PLANE AZ CUT
$\phi_c = -0.300"$

CO-POL. : P0007
X-POL. : P0008

14dB HORN PRIMARY
H-PLANE AZ CUT
ϕ_c =-0.990"

CO-POL. : P0009
X-POL. : P0010

14dB HORN PRIMARY
45° PLANE AZ CUT
ϕ_c =-0.990"

CO-POL. : P0011
X-POL. : P0012

LSST - II
PRELIMINARY FOCUS DATA
SECONDARY PATTERN LOG

CONFIGURATION	HORN	FEED AXIAL POSITION	POL.	PEAK GAIN (dB1)	PATTERN	PAGE NUMBER
	6 dB	0.0"*	CO	50.36	$\pm$ 5° AZ	32
	6 dB	0.0"	CO	"	$\pm$ 5° EL	33
	6 dB	+0.4"	CO	50.70	$\pm$ 5° AZ	34
	6 dB	+0.4"	CO	"	$\pm$ 5° EL	35
	6 dB	+0.8"	CO	50.83	$\pm$ 5° AZ	36
	6 dB	+0.8"	CO	"	$\pm$ 5° EL	37
	6 dB	+1.2"#	CO	50.85	$\pm$ 5° AZ	38
	6 dB	+1.2"	CO	"	$\pm$ 5° EL	39
	6 dB	+1.6"	CO	50.77	$\pm$ 5° AZ	40
	6 dB	+1.6"	CO	"	$\pm$ 5° EL	41
	6 dB	+1.8"	CO	50.66	$\pm$ 5° AZ	42
	6 dB	+1.8"	CO	"	$\pm$ 5° EL	43
	6 dB	+2.0"	CO	50.50	$\pm$ 5° AZ	44
	6 dB	+2.0"	CO	"	$\pm$ 5° EL	45
	14 dB	0.0"*	CO	50.00	$\pm$ 5° AZ	46
	14 dB	0.0"	CO	"	$\pm$ 5° EL	47
	14 dB	+0.8"	CO	50.48	$\pm$ 5° AZ	48
	14 dB	+0.8"	CO	"	$\pm$ 5° EL	49
	14 dB	+1.2"#	CO	50.52	$\pm$ 5° AZ	50
	14 dB	+1.2"	CO	"	$\pm$ 5° EL	51
	14 dB	+1.6"	CO	50.37	$\pm$ 5° AZ	52
	14 dB	+1.6"	CO	"	$\pm$ 5° EL	53
	14 dB	+1.8"	CO	50.35	$\pm$ 5° AZ	54
	14 dB	+1.8"	CO	"	$\pm$ 5° EL	55
	14 dB	+2.0"	CO	50.36	$\pm$ 5° AZ	56
	14 dB	+2.0"	CO	"	$\pm$ 5° EL	57

* Z' = 0.0" is the mechanical focus position as determined
with alignment tool.

\# Z' = +1.2" is the range corrected focus position used
for all secondary measurements.

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. AZ CUT
Z'=0.0"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. EL CUT
Z'=0.0"

-33-

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. AZ CUT
Z'=+0.4"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. EL CUT
Z'=+0.4"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. AZ CUT
Z'= +0.8"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. EL CUT
Z' = +0.8"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. AZ CUT
Z'= +1.2"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. EL CUT
Z'= +1.2"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. AZ CUT
Z'=+1.6"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. EL CUT
Z'= +1.6"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. AZ CUT
$Z' = +1.8"$

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. EL CUT
Z'= +1.8"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. AZ CUT
Z' = +2.0"

PRELIMINARY
FOCUS DATA

6dB HORN
CO-POL. EL CUT
Z' = +2.0"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. AZ CUT
Z'=0.0"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. EL CUT
Z'=0.0"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. AZ CUT
Z' = +0.8"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. EL CUT
Z' = +0.8"

SCIENTIFIC-ATLANTA, INC., ATLANTA, GEORGIA

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. AZ CUT
Z'= +1.2"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. EL CUT
Z'= +1.2"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. AZ CUT
Z'= +1.6"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. EL CUT
Z'= +1.6"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. AZ CUT
Z'= +1.8"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. EL CUT
Z'= +1.8"

PRELIMINARY FOCUS DATA

14dB HORN
CO-POL. AZ CUT
Z' = +2.0"

PRELIMINARY
FOCUS DATA

14dB HORN
CO-POL. EL CUT
Z' = +2.0"

LSST - III

RASTER SCAN LOG

CONFIG.	HORN	SCAN	POL.	PK. GAIN	AZIMUTH	ELEVATION	FILE NAME	PAGE NO.
	6 dB	0.0"	CO	50.75	$+2^{o}$	$+2^{o}$	RAST 07	59 - 61
	6 dB	0.0"	X	-	$+2^{o}$	$+2^{o}$	RAST 08	62 - 64
	6 dB	4.5"	CO	50.55	$+2^{o}$	$+2^{o}$	RAST 09	65 - 67
	6 dB	4.5"	X	-	$+2^{o}$	$+2^{o}$	RAST 10	68 - 70
	6 dB	0.0"	CO	50.75	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 17	71 - 73
	6 dB	0.0"	X	-	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 18	74 - 76
	6 dB	4.5"	CO	50.45	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 15	77 - 79
	6 dB	4.5"	X	-	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 16	80 - 82
	6 dB	0.0"	CO		-6^{o} to $+2^{o}$	$+2^{o}$	RAST 35	83 - 85
	14 dB	0.0"	CO	50.52	$+2^{o}$	$+2^{o}$	RAST 01	86 - 88
	14 dB	0.0"	X	-	$+2^{o}$	$+2^{o}$	RAST 02	89 - 91
	14 dB	4.5"	CO	50.35	$+2^{o}$	$+2^{o}$	RAST 05	92 - 94
	14 dB	4.5"	X	-	$+2^{o}$	$+2^{o}$	RAST 06	95 - 97
	14 dB	6.5"	CO	50.05	$+2^{o}$	$+2^{o}$	RAST 03	98 - 100
	14 dB	6.5"	X	-	$+2^{o}$	$+2^{o}$	RAST 04	101 - 103
	14 dB	0.0"	CO	50.39	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 11	104 - 106
	14 dB	0.0"	X	-	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 12	107 - 109
	14 dB	4.5"	CO	50.00	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 13	110 - 112
	14 dB	4.5"	X	-	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 14	113 - 115
	14 dB	0.0"	CO	50.55	-6^{o} to $+2^{o}$	$+2^{o}$	RAST 36	116 - 118

6 dB HORN

Scan: 0.0"

Co-Pol RASTER 07

6 dB   HORN

Scan: 0.0"

Co-Pol   RASTER 07

dB

AZ

6 dB   HORN

Scan: 0.0"

Co-Pol   RASTER 07

dB

EL

6 dB · HORN

Scan: 0.0"

X-Pol   RASTER 08

-27.6

-47.6

dB

-67.6

-87.6

-2.0

0.0

2.0

EL

2.0

0.0

-2.0

2.0

0.0

-2.0

AZ

6 dB   HORN

Scan: 0.0"

X-Pol   RASTER 08

dB

AZ

6 dB   HORN

Scan: 0.0"

X-Pol   RASTER 08

dB

-27.6

-47.6

-67.6

-87.6

-2.0   0.0   2.0

EL

VHIGH= -3.4000
VLOW=-78.3000
CEILING= 0.0000
FLOOR=-60.0000

6 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 0

0.0

-20.0

dB

-40.0

-60.0

-2.0

0.0

2.0

EL

2.0

-2.0

0.0

AZ

2.0

6 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 09

6 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 09

0.0

-20.0

dB

-40.0

-60.0

-2.0   0.0   2.0

EL

6 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 10

6 dB   HORN

SCAN: 4.5"

X-Pol.   RASTER 10

-27.1

-47.1

dB

-67.1

-87.1

-2.0   0.0   2.0

AZ

6 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 10

-27.1

-47.1

dB

-67.1

-87.1

-2.0   0.0   2.0

EL

YHIGH- -3.1000
YLOW- -53.3000
CEILING- 0.0000
FLOOR- -60.0000

6 dB HORN

Scan: 0.0"

Co-Pol RASTER 17

0.0

-20.0

dB

-40.0

-60.0

-6.0   -4.0   -2.0   0.0   2.0

AZ

6 dB HORN

Scan: 0.0"

Co-Pol RASTER 17

6 dB   HORN

Scan: 0.0"

X-Pol   RASTER 18

dB

-26.9

-46.9

-66.9

-86.9

2.0

0.0

-2.0

-4.0

-6.0

-2.0

0.0

2.0

EL

AZ

6 dB   HORN

Scan: 0.0"

X-Pol   RASTER 18

-26.9

-46.9

dB

-66.9

-86.9

-6.0   -4.0   -2.0   0.0   2.0

AZ

YHIGH=-30.0000
YLOW=-86.2000
CEILING=-20.0000
FLOOR=-80.0000

6 dB   HORN

Scan: 0.0"

X-Pol   RASTER 18

-26.9

-46.9

dB

-66.9

-86.9

-2.0   0.0   2.0

EL

VHIGH= -3.5000
VLOW=-79.4000
CEILING= 0.0000
FLOOR=-60.0000

6 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 15

0.0

-20.0

dB

-40.0

-60.0

2.0

-2.0

0.0

2.0

-6.0

-4.0

-2.0

0.0

EL

AZ

6 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 15

0.0

-20.0

dB

-40.0

-60.0

-2.0   0.0   2.0

EL

6 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 16

-25.4

-45.4

dB

-65.4

-85.4

2.0

0.0

-2.0

-2.0

0.0

2.0

-4.0

-6.0

EL

AZ

6 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 16

-25.4

-45.4

dB

-65.4

-85.4

-6.0   -4.0   -2.0   0.0   2.0

AZ

6 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 16

-25.4

-45.4

dB

-65.4

-85.4

-2.0   0.0   2.0

EL

6 dB HORN

SCAN: 0.0"

Co-Pol. RASTER 35

0.0

-20.0

dB

-40.0

-60.0

2.0

0.0

-2.0

-4.0

-6.0

-2.0

0.0

2.0

EL

AZ

6 dB HORN

SCAN: 0.0"

Co-Pol. RASTER 35

dB

AZ

6 dB HORN

SCAN: 0.6"

Co-Pol. RASTER 35

EL

14 dB HORN

Scan: 0.0"

Co-Pol. RASTER 01

dB

14 dB HORN

Scan: 0.0"

Co-Pol. Raster 01

dB

0.0

-20.0

-40.0

-60.0

-2.0   0.0   2.0

EL

14 dB HORN

Scan: 0.0"

X-Pol   RASTER 02

14 dB HORN

Scan: 0.0"

X-Pol   RASTER 02

-31.0

-51.0

dB

-71.0

-91.0

-2.0   0.0   2.0

AZ

14 dB HORN

Scan: 0.0"

X-Pol RASTER 02

-31.0

-51.0

dB

-71.0

-91.0

-2.0   0.0   2.0

EL

14 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 05

14 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 05

0.0

-20.0

dB

-40.0

-60.0

-2.0   0.0   2.0

EL

14 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 06

14 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 06

-30.0

-50.0

dB

-70.0

-90.0

-2.0   0.0   2.0

AZ

14 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 06

-30.0

-50.0

dB

-70.0

-90.0

-2.0   0.0   2.0

EL

YHIGH= -2.4000
YLOW=-76.9000
CEILING= 0.0000
FLOOR=-60.0000

14 dB HORN

SCAN: 6.5"

Co-Pol. RASTER 03

0.0

-20.0

dB

-40.0

-60.0

-2.0

0.0

2.2

-2.0

0.0

2.0

EL

AZ

14 dB HORN

SCAN: 6.5"

Co-Pol.   RASTER 03

AZ

14 dB HORN

SCAN: 6.5"

Co-Pol. RASTER 03

14 dB HORN

SCAN: 6.5"

X Pol.   RASTER 04

-31.6

-51.6

dB

-71.6

-91.6

2.0

-2.0

0.0

EL

2.0

-2.0

0.0

2.0

AZ

14 dB HORN

SCAN: 6.5"

X-Pol.   RASTER 04

-31.6

-51.6

dB

-71.6

-91.6

-2.0   0.0   2.0

AZ

14 dB HORN

SCAN: 6.5"

X Pol.   RASTER 04

EL

14 dB HORN

Scan: 0.0"

Co-Pol RASTER 11

YHIGH- -3.4000
YLOU--82.6000
CEILING: 0.0000
FLOOR--60.0000

14 dB HORN

Scan: 0.0"

Co-Pol   RASTER 11

0.0

-20.0

dB

-40.0

-60.0

-2.0   0.0   2.0

EL

14 dB HORN

Scan: 0.0"

X-Pol RASTER 12

-28.9

-48.9

dB

-68.9

-88.9

2.0

0.0

-2.0

-2.0

0.0

-4.0

EL

0.0

2.0

-2.0

-6.0

AZ

14 dB HORN

Scan: 0.0"

X-Pol   RASTER 12

-28.9

-48.9

dB

-68.9

-88.9

-6.0   -4.0   -2.0   0.0   2.0

AZ

14 dB HORN

Scan: 0.0"

X-Pol   RASTER 12

dB

-28.9

-48.9

-68.9

-88.9

-2.0   0.0   2.0

EL

YHIGH= -3.5000
YLOW=-83.4000
CEILING= 0.0000
FLOOR=-60.0000

14 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 13

YHIGH= -3.5000
VLOW=-83.4000
CEILING= 0.0000
FLOOR=-60.0000

0.0

-20.0

dB

-40.0

-60.0

-6.0   -4.0   -2.0   0.0   2.0

AZ

14 dB HORN

SCAN: 4.5"

Co-Pol.   RASTER 13

EL

14 dB HORN

SCAN: 4.5"
X-Pol.   RASTER 14

-27.2

-47.2

dB

-67.2

-87.2

2.0

0.0

-2.0

-4.0

-6.0

-2.0

0.0

6.0

EL

AZ

14 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 14

dB

-27.2

-47.2

-67.2

-87.2

-6.0   -4.0   -2.0   0.0   2.0

AZ

14 dB HORN

SCAN: 4.5"

X-Pol.   RASTER 14

-27.2

-47.2

dB

-67.2

-67.2

-2.0   0.0   2.0

EL

14 dB HORN

SCAN: 0.0"

Co-Pol.   RASTER 36

dB

0.0

-20.0

-40.0

-60.0

2.0

0.0

-2.0

-4.0

-6.0

02.0

0.0

2.0

EL

AZ

14 dB HORN

SCAN: 0.0"

Co-Pol.   RASTER 36

0.0

-20.0

dB

-40.0

-60.0

-6.0   -4.0   -2.0   0.0   2.0

AZ

14 dB HORN

SCAN: 0.0"

Co-Pol.   RASTER 36

CONFIGURATION	HORN	SCAN	POL.	PK. GAIN	PATTERN	FILE NAME	PAGE NUMBER
	6 dB	0.0"	CO	50.85	$\pm$ 45° AZ	L0001	120
	"	"	CO	"	$\pm$ 5° AZ	L0002	121
	"	"	CO	"	$\pm$ 5° EL	L0003	122
	"	"	X	–	$\pm$ 45° AZ	L0004	123
	"	"	X	–	$\pm$ 5° AZ	L0005	124
	"	"	X	–	$\pm$ 5° EL	L0006	125
	6 dB	4.5"	CO	50.55	$\pm$ 45° AZ	L0027	126
	"	"	CO	"	$\pm$ 5° AZ	L0025	127
	"	"	CO	"	$\pm$ 5° EL	L0026	128
	"	"	X	–	$\pm$ 45° AZ	L0030	129
	"	"	X	–	$\pm$ 5° AZ	L0028	130
	"	"	X	–	$\pm$ 5° EL	L0029	131
	6 dB	0.0"	CO	35.25	$\pm$ 45° AZ	L0074	132
	"	"	CO	"	$\pm$ 5° AZ	L0073	133
	"	"	CO	"	$\pm$ 5° EL	L0075	134
	"	"	X	–	$\pm$ 45° AZ	L0078	135
	"	"	X	–	$\pm$ 5° AZ	L0077	136
	"	"	X	–	$\pm$ 5° EL	L0076	137
	6 dB	0.0"	CO	34.65	$\pm$ 45° AZ	L0079	138
	"	"	CO	"	$\pm$ 5° AZ	L0080	139
	"	"	CO	"	$\pm$ 5° EL	L0081	140
	"	"	X	–	$\pm$ 45° AZ	L0084	141
	"	"	X	–	$\pm$ 5° AZ	L0083	142
	"	"	X	–	$\pm$ 5° EL	L0082	143
	6 dB	0.0"	CO	50.75	$\pm$ 45° AZ	L0051	144
	"	"	CO	"	$\pm$ 5° AZ	L0049	145
	"	"	CO	"	$\pm$ 5° EL	L0050	146
	"	"	X	–	$\pm$ 45° AZ	L0054	147
	"	"	X	–	$\pm$ 5° AZ	L0052	148
	"	"	X	–	$\pm$ 5° EL	L0053	149

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0001

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0002

6dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0003

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0004

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0005

6dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0006

6dB HORN
SCAN: 4.5" IN
CO-POL. AZ CUT
L0027

6dB HORN
SCAN: 4.5"
CO-POL. AZ CUT
L0025

6dB HORN
SCAN: 4.5"
CO-POL. EL CUT
LC026

6dB HORN
SCAN: 4.5" IN
X-POL. AZ CUT
L0030

6dB HORN
SCAN: 4.5"
X-POL. AZ CUT
L0028

6dB HORN
SCAN: 4.5"
X-POL. EL CUT
L0029

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0074

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0073

6dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0075

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0078

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0077

SCIENTIFIC-ATLANTA, INC. ATLANTA, GEORGIA

6dB HORN
SCAN: 0.0°
X-POL. EL CUT
L0076

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0079

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0080

6dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0081

SCIENTIFIC-ATLANTA, INC., ATLANTA, GEORGIA   CHART NO. 141

6dB HORN

SCAN: 0.0"

X-POL. AZ CUT

L0084

6dB HORN
SCAN: 0.0"
X-POL, PZ CUT
L0083

6dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0082

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0051

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0049

6dB HORN
SCAN: 0.0"
CO-POL. EL CUT
LC050

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0054

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0052

6dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0053

LSST - V

SECONDARY PATTERN LOG

CONFIGURATION	HORN	SCAN	POL.	PK. GAIN	PATTERN	FILE NAME	PAGE NUMBER
	6 dB	0.0	CO	–	$+3^{\circ}$EL $\pm$ 45°AZ	R3301	151
	"	"	"	–	$+2^{\circ}$EL "	R3302	152
	"	"	"	–	$+1^{\circ}$EL "	R3303	153
	"	"	"	50.75	0°EL "	R3304	154
	"	"	"	–	-1°EL "	R3305	155
	"	"	"	–	-2°EL "	R3306	156
	"	"	"	–	-3°EL "	R3307	157
	6 dB	0.0	X	–	$+3^{\circ}$EL $\pm$ 45°AZ	R3401	158
	"	"	"	–	$+2^{\circ}$EL "	R3402	159
	"	"	"	–	$+1^{\circ}$EL "	R3403	160
	"	"	"	–	0°EL "	R3404	161
	"	"	"	–	-1°EL "	R3405	162
	"	"	"	–	-2°EL "	R3406	163
	"	"	"	–	-3°EL "	R3407	164
	6 dB	4.5"	CO	50.45	$+45^{\circ}$ AZ	L0045	165
	"	"	CO	"	$\pm 5^{\circ}$ AZ	L0043	166
	"	"	CO	"	$\pm 5^{\circ}$ EL	L0044	167
	"	"	X	"	$+45^{\circ}$ AZ	L0048	168
	"	"	X	"	$\pm 5^{\circ}$ AZ	L0046	169
	"	"	X	"	$\pm 5^{\circ}$ EL	L0047	170
	6 dB	0.0	CO	–	$+3^{\circ}$EL $\pm$ 45°AZ	R3101	171
	"	"	"	–	$+2^{\circ}$EL "	R3102	172
	"	"	"	–	$+1^{\circ}$EL "	R3103	173
	"	"	"	50.70	0°EL "	R3104	174
	"	"	"	–	-1°EL "	R3105	175
	"	"	"	–	-2°EL "	R3106	176
	"	"	"	–	-3°EL "	R3107	177
	6 dB	0.0	X	–	$+3^{\circ}$EL $\pm$ 45°AZ	R3201	178
	"	"	"	–	$+2^{\circ}$EL "	R3202	179
	"	"	"	–	$+1^{\circ}$EL "	R3203	180
	"	"	"	–	0°EL "	R3204	181
	"	"	"	–	-1°EL "	R3205	182
	"	"	"	–	-2°EL "	R3206	183
	"	"	"	–	-3°EL "	R3207	184

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+3.0°
R3301

6db HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+2.0°
R3302

SCIENTIFIC-ATLANTA, INC., ATLANTA, GEORGIA

CHART NO. 16

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+1.0°
R3303

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=0.0°
R3304

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-1.0°
R3305

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-2.0°
R3306

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-3.0°
R3307

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+3.0°
R3401

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+2.0°
R3402

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+1.0°
R3403

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=0.0°
R3404

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-1.00°
R3405

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-2.0°
R3406

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-3.0°
R3407

6dB HORN
SCAN: 4.5" IN
CO-POL. AZ CUT
L0045

6dB HORN
SCAN: 4.5" IN
CO-POL. AZ CUT
L0043

6dB HORN
SCAN: 4.5" IN
CO-POL. EL CUT
L0044

6dB HORN
SCAN: 4.5" IN
X-POL. AZ CUT
L0048

6dB HORN
SCAN: 4.5" IN
X-POL. AZ CUT
L0046

6dB HORN
SCAN: 4.5" IN
X-POL. EL CUT
L0047

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+3.0°
R3101

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+2.0°
R3102

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+1.0°
R3103

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=0.0°
R3104

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-1.0°
R3105

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-2.0°
R3106

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-3.0°
R3107

6dB HORN
SCAN: 0.0"
X=POL. AZ CUT

EL=+3.0°
R3201

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+2.0°
R3202

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+1.0°
R3203

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=0.0°
R3204

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-1.0°
R3205

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-2.0°
R3206

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-3.0°
R3207

LSST - VI

SECONDARY PATTERN LOG

CONFIGURATION	HORN	SCAN	POL.	PK. GAIN	PATTERN	FILE NAME	PAGE NUMBER
	6 dB	0.0"	CO	–	+3^{o}EL $\pm$ 45^{o}AZ	R2901	186
	"	"	"	–	+2^{o}EL "	R2902	187
	"	"	"	–	+1^{o}EL "	R2903	188
	"	"	"	50.80	0^{o}EL "	R2904	189
	"	"	"	–	–1^{o}EL "	R2905	190
	"	"	"	–	–2^{o}EL "	R2906	191
	"	"	"	–	–3^{o}EL "	R2907	192
	6 dB	0.0"	X	–	+3^{o}EL $\pm$ 45^{o}AZ	R3001	193
	"	"	"	–	+2^{o}EL "	R3002	194
	"	"	"	–	+1^{o}EL "	R3003	195
	"	"	"	–	0^{o}EL "	R3004	196
	"	"	"	–	–1^{o}EL "	R3005	197
	"	"	"	–	–2^{o}EL "	R3006	198
	"	"	"	–	–3^{o}EL "	R3007	199
	6 dB	0.0"	CO	–	+3^{o}EL $\pm$ 45^{o}AZ	R2701	200
	"	"	"	–	+2^{o}EL "	R2702	201
	"	"	"	–	+1^{o}EL "	R2703	202
	"	"	"	50.65	0^{o}EL "	R2704	203
	"	"	"	–	–1^{o}EL "	R2705	204
	"	"	"	–	–2^{o}EL "	R2706	205
	"	"	"	–	–3^{o}EL "	R2707	206
	6 dB	0.0"	X	–	+3^{o}EL $\pm$ 45^{o}AZ	R2801	207
	"	"	"	–	+2^{o}EL "	R2802	208
	"	"	"	–	+1^{o}EL "	R2803	209
	"	"	"	–	0^{o}EL "	R2804	210
	"	"	"	–	–1^{o}EL "	R2805	211
	"	"	"	–	–2^{o}EL "	R2806	212
	"	"	"	–	–3^{o}EL "	R2807	213

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+3.0°
R2901

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+2.0°
R2902

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+1.0°
R2903

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=0.0°
R2904

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-1.0°
R2905

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-2.0°
R2906

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-3.0°
R2907

6dB HORN
SCAN: 6.0"
X-POL, AZ CUT

EL=+3.0°
R3001

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+2.0°
R3002

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+1.0°
R3003

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=0.0°
R3004

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-1.0°
R3005

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-2.0°
R3006

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-3.0°
R3007

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+3.0°
R2701

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+2.0°
R2702

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+1.0°
R2703

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=0.0°
R2704

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-1.0°
R2705

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-2.0°
R2706

6dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-3.0°
L2707

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+3.0°
R2801

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+2.0°
R2802

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+1.0°
R2803

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=0.0°
R2804

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-1.0°
R2805

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-2.0°
R2806

6dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-3.0°
R2807

LSST - VII

SECONDARY PATTERN LOG

CONFIGURATION	HORN	SCAN	POL.	PK. GAIN	PATTERN	FILE NAME	PAGE NUMBER
	14 dB	0.0"	CO	50.52	$\pm$ 45° AZ	L0007	215
	"	"	CO	"	$\pm$ 5° AZ	L0008	216
	"	"	CO	"	$\pm$ 5° EL	L0009	217
	"	"	X	–	$\pm$ 45° AZ	L0010	218
	"	"	X	–	$\pm$ 5° AZ	L0011	219
	"	"	X	–	$\pm$ 5° EL	L0012	220
	14 dB	4.5"	CO	50.35	$\pm$ 45° AZ	L0017	221
	"	"	CO	"	$\pm$ 5° AZ	L0015	222
	"	"	CO	"	$\pm$ 5° EL	L0016	223
	"	"	X	–	$\pm$ 45° AZ	L0020	224
	"	"	X	–	$\pm$ 5° AZ	L0018	225
	"	"	X	–	$\pm$ 5° EL	L0019	226
	14 dB	6.5"	CO	50.05	$\pm$ 45° AZ	AAN45	227
	"	"	CO	"	$\pm$ 5° AZ	AANC1	228
	"	"	CO	"	$\pm$ 5° EL	EANC1	229
	"	"	X	–	$\pm$ 45° AZ	AXPSC	230
	"	"	X	–	$\pm$ 5° AZ	AZPSC	231
	"	"	X	–	$\pm$ 5° EL	EXPSC	232
	14 dB	0.0"	CO	32.15	$\pm$ 45° AZ	L0068	233
	"	"	CO	"	$\pm$ 5° AZ	L0067	234
	"	"	CO	"	$\pm$ 5° EL	L0069	235
	"	"	X	–	$\pm$ 45° AZ	L0072	236
	"	"	X	–	$\pm$ 5° AZ	L0071	237
	"	"	X	–	$\pm$ 5° EL	L0070	238
	14 dB	0.0"	CO	35.05	$\pm$ 45° AZ	L0063	239
	"	"	CO	"	$\pm$ 5° AZ	L0061	240
	"	"	CO	"	$\pm$ 5° EL	L0062	241
	"	"	X	–	$\pm$ 45° AZ	L0066	242
	"	"	X	–	$\pm$ 5° AZ	L0065	243
	"	"	X	–	$\pm$ 5° EL	L0064	244

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0007

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0008

14dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0009

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0010

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0011

14dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0012

14dB HORN
SCAN: 4.5" IN
CO-POL, AZ CUT
L0017

14dB HORN
SCAN: 4.5"
CO-POL. AZ CUT
L0015

14dB HORN
SCAN: 4.5" IN
CO-POL. EL CUT
L0016

14dB HORN
SCAN: 4.5" IN
X-POL. AZ CUT
L0020

14dB HORN
SCAN: 4.5" IN
X-POL. AZ CUT
L0018

14dB HORN
SCAN: 4.5"
X-POL. EL CUT
L0019

14dB HORN
SCAN: 6.5"
CO-POL. AZ CUT
AAN45

14dB HORN
SCAN: 6.5"
CO-POL. AZ CUT
AANC1

14dB HORN
SCAN: 6.5"
CO-POL. EL CUT
EANC1

14dB HORN
SCAN: 6.5"
X-POL. AZ CUT
AXPSC

14dB HORN
SCAN: 6.5"
X-PCL. AZ CUT
AZPSC

14dB HORN
SCAN: 6.5"
X-POL. EL CUT
EXPSC

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0068

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0067

14dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0069

14dB HORN
SCAN: 0.0
X-POL, AZ CUT
L0072

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0071

14dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0070

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0063

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0061

14dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0062

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0066

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0065

14dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0064

LSST - VIII

SECONDARY PATTERN LOG

CONFIGURATION	HORN	SCAN	POL.	PK. GAIN	PATTERN	FILE NAME	PAGE NUMBER
	14 dB	0.0"	CO	50.39	$\pm$ 45° AZ	L0033	246
	"	"	CO	"	$\pm$ 5° AZ	L0031	247
	"	"	CO	"	$\pm$ 5° EL	L0032	248
	"	"	X	–	$\pm$ 45° AZ	L0035	249
	"	"	X	–	$\pm$ 5° AZ	L0034	250
	"	"	X	–	$\pm$ 5° EL	L0036	251
	14 dB	0.0"	CO	–	+3°EL $\pm$ 45°AZ	R2101	252
	"	"	"	–	+2°EL "	R2102	253
	"	"	"	–	+1°EL "	R2103	254
	"	"	"	50.55	0°EL "	R2104	255
	"	"	"	–	−1°EL "	R2105	256
	"	"	"	–	−2°EL "	R2106	257
	"	"	"	–	−3°EL "	R2107	258
	14 dB	0.0"	X	–	+3°EL $\pm$ 45°AZ	R2201	259
	"	"	"	–	+2°EL "	R2202	260
	"	"	"	–	+1°EL "	R2203	261
	"	"	"	–	0°EL "	R2204	262
	"	"	"	–	−1°EL "	R2205	263
	"	"	"	–	−2°EL "	R2206	264
	"	"	"	–	−3°EL "	R2207	265
	14 dB	4.5"	CO	50.00	$\pm$ 45° AZ	L0039	266
	"	"	CO	"	$\pm$ 5° AZ	L0037	267
	"	"	CO	"	$\pm$ 5° EL	L0038	268
	"	"	X	–	$\pm$ 45° AZ	L0042	269
	"	"	X	–	$\pm$ 5° AZ	L0040	270
	"	"	X	–	$\pm$ 5° EL	L0041	271
	14 dB	0.0"	CO	50.55	$\pm$ 45° AZ	L0057	272
	"	"	CO	"	$\pm$ 5° AZ	L0055	273
	"	"	CO	"	$\pm$ 5° EL	L0056	274
	"	"	X	–	$\pm$ 45° AZ	L0060	275
	"	"	X	–	$\pm$ 5° AZ	L0058	276
	"	"	X	–	$\pm$ 5° EL	L0059	277

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0033

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0031

14dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0032

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0035

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0034

14dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0036

14dB HORN
SCAN: 0.0°
CO-POL. AZ CUT

EL=+3.0°
R2161

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+2.0°
R2102

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+1.0°
R2103

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=0.0°
R2104

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-1.0°
R2105

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-2.0°
R2106

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-3.0°
R2107

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+3.0°
R2201

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+2.0°
R2202

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+1.0°
R2203

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=0.0°
R2204

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-1.0°
R2205

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-2.0°
R2206

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-3.0°
R2207

14dB HORN
SCAN: 4.5" IN
CO-POL. AZ CUT
L0039

14dB HORN
SCAN: 4.5" IN
CO-POL. AZ CUT
L0037

14dB HORN
SCAN: 4.5" IN
CO-POL.. EL CUT
LC038

14dB HORN
SCAN: 4.5" IN
X-POL. AZ CUT
L0042

14dB HORN
SCAN: 4.5"
X-POL. AZ CUT
L0040

14dB HORN
SCAN: 4.5" IN
X-POL. EL CUT
L0041

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0057

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
L0055

14dB HORN
SCAN: 0.0"
CO-POL. EL CUT
L0056

-274-

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
L0060

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
LOC58

14dB HORN
SCAN: 0.0"
X-POL. EL CUT
L0059

LSST - IX

| CONFIGURATION	HORN	SCAN	POL.	PK. GAIN	PATTERN	FILE NAME	PAGE NUMBER
	14 dB	0.0"	CO	–	$+3^O$EL $\pm$ 45^O AZ	R1901	279
	"	"	"	–	$+2^O$EL "	R1902	280
	"	"	"	–	$+1^O$EL "	R1903	281
	"	"	"	50.55	0^OEL "	R1904	282
	"	"	"	–	-1^OEL "	R1905	283
	"	"	"	–	-2^OEL "	R1906	284
	"	"	"	–	-3^OEL "	R1907	285
	14 dB	0.0"	X	–	$+3^O$EL $\pm$ 45^OAZ	R2001	286
	"	"	"	–	$+2^O$EL "	R2002	287
	"	"	"	–	$+1^O$EL "	R2003	288
	"	"	"	–	0^OEL "	R2004	289
	"	"	"	–	-1^OEL "	R2005	290
	"	"	"	–	-2^OEL "	R2006	291
	"	"	"	–	-3^OEL "	R2007	292
	14 dB	0.0"	CO	–	$+3^O$EL $+45^O$AZ	R2501	293
	"	"	"	–	$+2^O$EL "	R2502	294
	"	"	"	–	$+1^O$EL "	R2503	295
	"	"	"	50.35	0^OEL "	R2504	296
	"	"	"	–	-1^OEL "	R2505	297
	"	"	"	–	-2^OEL "	R2506	298
	"	"	"	–	-3^OEL "	R2507	299
	14 dB	0.0"	X	–	$+3^O$EL $\pm$ 45^OAZ	R2601	300
	"	"	"	–	$+2^O$EL "	R2602	301
	"	"	"	–	$+1^O$EL "	R2603	302
	"	"	"	–	0^OEL "	R2604	303
	"	"	"	–	-1^OEL "	R2605	304
	"	"	"	–	-2^OEL "	R2606	305
	"	"	"	–	-3^OEL "	R2607	306

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+3.0°
R1901

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+2.0°
R1902

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+1.0°
R1903

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=0.0°
R1904

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-1.0°
R1905

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-2.0°
R1906

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-3.0°
R1907

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+3.0°
R2001

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+2.0°
R2002

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+1.0°
R2003

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=0.0°
R2004

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-1.0°
R2005

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-2.0°
R2006

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-3.0°
R2007

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+3.0°
R2501

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=+2.0°
R2502

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+1.0°
R2503

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=0.0°
R2504

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-1.0°
R2505

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-2.0°
R2506

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL= -3.0°
R2507

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+3.00°
R2601

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+2.0°
R2602

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+1.0°
R2603

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=0.0
R2604

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-1.0°
R2605

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-2.0°
R2606

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-3.0°
R2607

LSST – X

SECONDARY PATTERN LOG

| CONFIGURATION	HORN	SCAN	POL.	PK. GAIN	PATTERN		FILE NAME	PAGE NUMBER
	14 dB	0.0"	CO	–	$+3^{\circ}$EL $\pm$ 45°AZ		R2301	308
	"	"	"	–	$+2^{\circ}$EL	"	R2302	309
	"	"	"	–	$+1^{\circ}$EL	"	R2303	310
	"	"	"	50.50	0°EL	"	R2304	311
	"	"	"	–	-1°EL	"	R2305	312
	"	"	"	–	-2°EL	"	R2306	313
	"	"	"	–	-3°EL	"	R2307	314
	14 dB	0.0"	X	–	$+3^{\circ}$EL	"	R2401	315
	"	"	"	–	$+2^{\circ}$EL	"	R2402	316
	"	"	"	–	$+1^{\circ}$EL	"	R2403	317
	"	"	"	–	0°EL	"	R2404	318
	"	"	"	–	-1°EL	"	R2405	319
	"	"	"	–	-2°EL	"	R2406	320
	"	"	"	–	-3°EL	"	R2407	321

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+3.0°
R2301

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+2.0°
R2302

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=+1.0°
R2303

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=0.0°
R2304

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-1.0°
R2305

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT
EL=-2.0°
R2306

14dB HORN
SCAN: 0.0"
CO-POL. AZ CUT

EL=-3.0°
R2307

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=+3.00°
R2401

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+2.0°
R2402

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=+1.0°
R2403

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=0.0°
R2404

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-1.0°
R2405

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT

EL=-2.0°
R2406

14dB HORN
SCAN: 0.0"
X-POL. AZ CUT
EL=-3.0°
R2407

| 1. Report No. NASA CR-172412	2. Government Accession No.	3. Recipient's Catalog No.
4. Title and Subtitle Hoop/Column Antenna - RF Verification Model Volume I - Test Results		5. Report Date August 1984
		6. Performing Organization Code
7. Author(s) W. F. Croswell (Editor), M. D. Vanstrum, R. J. Schrimpf, R. G. Taylor, and R. L. Moye		8. Performing Organization Report No.
		10. Work Unit No.
9. Performing Organization Name and Address Harris Corporation Government Electronic Systems Division P. O. Box 9400 Melbourne, FL 32902		11. Contract or Grant No. NAS 1-15763
		13. Type of Report and Period Covered Contractor Report Jan. to Aug. 1983
12. Sponsoring Agency Name and Address National Aeronautics and Space Administration Washington, DC 20546		14. Sponsoring Agency Code 506-62-43-01

15. Supplementary Notes

Langley Technical Monitor: Thomas G. Campbell
Final Report

16. Abstract

As part of the Large Space System Technology Program, this report, in two volumes, presents the theoretical and experimental results of the RF characteristic of a hoop/column, quad aperture antenna using an RF verification model.

To satisfy the primary purposes of the model it provides experimental pattern data for the quad aperture configuration at different reflector edge illumination levels, from which the geometry and edge effects can be assessed, and provides experimental data which can be compared with calculations using various theoretical reflector scattering formulae. It also experimentally determines the effects upon secondary patterns of scale model quartz cables, as used in the hoop/column design, upon secondary patterns in order to assess the importance of developing a scattering theory to predict such effects. In addition, this report contains a comprehensive theoretical study and the experimental pattern results of quad aperture antenna feeds, a discussion of the fundamental affect of parasitic side lobes, their amplitude, and location in space.

17. Key Words (Suggested by Author(s)) Antenna Parabolic Reflector Quad Aperture Hoop/Column Feeds	18. Distribution Statement Unclassified - Unlimited Subject Category 32

19. Security Classif. (of this report) Unclassified	20. Security Classif. (of this page) Unclassified	21. No. of Pages 322	22. Price A14